

British Manufacturing since 1957



The Professionals Choice

CTS5

SureFlow Compact Counter-Top Boiler



FULL SPECIFICATION



SureFlow Compact Counter-Top, Automatic-Fill Water Boiler

| Tuno | Countarian Standard Dance |
|---|---|
| Type | Countertop - Standard Range |
| Country of Design & Manufacture | UK |
| CAPACITY, WEIGHTS & DIMENSIONS: | 5 |
| Capacity (Litres) | 5 |
| Unit dimensions (W x D x H) mm | 218 x 465 x 440 (depth includes drip-tray) |
| Packed dimensions (W x D x H) mm | 335 x 560 x 650 |
| Tap clearance mm | 150mm |
| Product weight - empty (kg) | 9.7 |
| Product weight – full (kg) | 16.0 |
| Packed weight (kg) | 12.0 |
| CONSTRUCTION: | |
| Outer fabrication (body) construction | 304 grade Stainless Steel (Superbrush polish) |
| Tank construction | 304 & 316 grade Stainless Steel |
| Tank wall thickness | 0.9mm |
| Drip-tray | 304 grade Stainless Steel – (Mirror polish) |
| ELECTRICAL: | |
| Power rating (kW) | 3 |
| Voltage supply | 230 V (50-60Hz) |
| Electrical supply | Single-phase, N & E (13A) |
| Plug type | UK standard 3-pin |
| Fitted cable length (m) | 1.7m |
| PLUMBING: | |
| Water inlet connection: | 3/4" BSP |
| Food quality, flexible mains water hose | 1.6 metre long, (3/4"BSP) |
| Mains water pressure range | 2 – 7 bar (28psi – 100psi) |
| Overflow/waste connection: | Front via drip-tray (or rear using kit not supplied) |
| PERFORMANCE: | , |
| Water temperature delivered | 96°C (default) – can be adjusted if required |
| Heat up time to working temperature | 15 mins (full tank capacity) |
| Output per hour (@ default temperature setting) | 28 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off | 5 Litres |
| Recovery per minute | 0.5 Litres |
| Stand-by power loss (idle mode) | 0.066 kW/h |
| FILTRATION: | 0.000 KWIII |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | No (available as an optional extra if required) |
| OTHER FEATURES: | 140 (available as all optional extra il requirea) |
| 7 day programmable timer | No |
| Energy-saving ECO mode | No |
| Tank-baffle plates – unique design aids heat recovery & | Yes |
| reduces steam emissions to atmosphere | 165 |
| Early warning lime-scale diagnostics (via LED light) | Yes – Basic |
| | |
| Dual safety protection | Yes - Over-boil & boil-dry protection |
| STANDARDS & APPROVALS: | Voc |
| WRAS approved | Yes |
| EMC Tested and Certified (EN 55014 & EN 61000) | Yes |
| Electrical Safety Tested and Certified to BS standard | Yes |
| EN 60335-1 & 2 | |
| WARRANTY & AFTER-SALES: | 0.7 |
| Guarantee | 2 Year parts & labour |
| Spare parts, filters & accessories | Same day despatch (if ordered before 3pm) |

Culligan Ireland

culligan.ie 1800 266 537 (Ireland) 0800 1026 349 (Northern Ireland) sales@culligan.ie





Certificate Numbers: FM01234 & EM01234